



TEXAS TEXFRIGE R SERIES

Synthetic Refrigerator Compressor Oil

PRODUCT DATA SHEET

Issued on 15th April 2016

Texas Petrochemical Asia Pacific Pte Ltd

80 International Road

Singapore 629170

Tel: 65-6262 6538

Fax: 65-6262 6537

Website: www.texaslub.com

DESCRIPTION

Texas Texfrige R series Compressor Oils are superior quality hydrocarbon lubricants which have excellent physical and chemical properties that make them especially well-suited for lubricating of refrigeration equipment.

Texas Texfrige R series has a high miscible with critical fluorocarbon refrigerants and can be used for very low temperature applications. The high degree of chemical and thermal stability of the lubricant ensures long service life and reliable performance with outstanding cleanliness.

BENEFITS

- High miscibility characteristics
- Extended Maintenance Intervals

TYPICAL APPLICATIONS

- Exceptionally well suited for use with fluorocarbon refrigerants and can be used with other common refrigerants as well.
- Can be used in open, semi-open and hermetic compressors in domestic, commercial and industrial refrigeration systems.
- Compatible with all sealing materials commonly used with fluorocarbon refrigerant systems.

TYPICAL PROPERTIES

ISO Grade	R32	R46	R68	R100
Density, kg/liter @ 15°C	0.98	0.97	0.96	0.96
Kinematic Viscosity, mm ² /s @ 40°C	30.4	45.1	66.9	98.8
Pour Point, °C	-55	-55	-45	-35
Flash Point COC, °C	195	200	210	210