

LEADING PROVIDER OF LUBRICANT SOLUTIONS



TEXAS LUBRICANT HEAVY-DUTY PRODUCT INTRODUCTION

TRITON RANGE DIESEL ENGINE OILS

Texas Triton range is designed to help engine withstand extreme conditions in both industrial and commercial applications. With performance standards that meets the highest OEM and API requirements. Texas Triton Range diesel engine oils will enable users to lower overall operating cost and downtime through its extended drain interval and engine protection capabilities.

Full product specifications, description and application can be requested from your local distributor.

1. TRITON TX 9 API CK-4

LATEST NEW GENERATION PREMIUM HD DIESEL ENGINE OIL

5W30 FULLY SYNTHETIC

10W40 SEMI SYNTHETIC

15W40 MINERAL

PERFORMANCE STANDARDS

- API CK-4, CJ-4, CI-4 PLUS, CI-4, CH-4 · Volvo VDS 4.5
- ACEA E9-16, E6-16 · Renault VI RLD-4
- Mack EOS-4.5 · MAN M3477* M3677**(5W30)
- JASO DH-2 · MB228.51+ M228.31++ (15W40)
- Cummins CES 20086 · Scania LDF-4**(5W30)

· Detroit Diesel DDC93K22

Currently available in 200L, 20L, 18L

2. ULTRA TRITON API CI-4/SL

ADVANCE HIGH-PERFORMANCE HD DIESEL ENGINE OIL

10W30 SEMI SYNTHETIC

10W40 SEMI SYNTHETIC

15W40 MINERAL

20W50 MINERAL

PERFORMANCE STANDARDS

- API CI4/SL · MAN 3275
- ACEA E7-16, A3/B4-16 (10W-40) · MTU Type II
- Duetz DQC-III · Volvo VDS 3
- Global DHD-1 · Cummins 20077/8
- MB P228.3 MB229.1(10W-40) · Mack EO-M Plus
- Detroit Diesel 93K215
- Caterpillar ECF 2, 1a

Currently available in 200L, 20L, 18L, 5L

3. TRITON SX5 CF-4/SG

ECONOMICAL HD DIESEL ENGINE OIL

15W40 MINERAL

20W50 MINERAL

PERFORMANCE STANDARDS

- API CF-4/SG

Recommended only for older vehicles *

Currently available in 200L, 20L, 18L, 5L, 4L, 1L



HYDRAULIC OILS

Texas Hydraulic oils are specially crafted to provide unparalleled performance and reliability for your hydraulic systems. An advanced formula is designed to protect against wear and tear, minimize deposit formation, and resist the detrimental effects of high temperatures and pressures. Texas Hydraulic oils boasts superior anti-foaming properties, excellent water separation, and effective rust and corrosion prevention with outstanding viscosity stability and low pour point ensure consistent fluidity in a range of operating temperatures.

Full product specifications, description and application can be requested from your local distributor.

1. TEXAS HYDRAULIC AW RANGE

STANDARD - HIGHLY RELIABLE - ECONOMICAL

ISO VG 32, 46, 68, 100

PERFORMANCE STANDARDS

- AFNOR NE E 48-603 HM
- Cincinnati Milacron P-68, P-69, P-70
- DIN 51 524 Part 2, ISO 11158 HM, SAE MS 1004 HM AND ASTM D6158HM
- Denison HF-0, HF-1, HF-2
- Vickers M-2950-S, I-286-S
- FZG A/8.3/90 LOAD STAGE 10

Currently available in 200L, 20L, 18L

2. HYDRAULIC HS(HVI) RANGE

HIGH VISCOSITY INDEX - WIDE-RANGE TEMPERATURE PERFORMANCE - LONG LIFE

ISO VG 15, 32, 46, 68, 100, 150

PERFORMANCE STANDARDS

- AFNOR NE E 48-603 HM · Sperry Vickers 1-286-S, M-2950-S (35VQ25)
- Cincinnati Milacron P68, P69, P70 · US Steel 136, 127
- DIN 51 524 Part 3 HVLP · CETOP and Pall Filterability
- Hagglunds Denison HF-2, HF-0 · NF E 48-690, NF E 48-691 Filterability

Currently available in 200L, 20L, 18L

3. HYDRAULIC ZF RANGE

ZINC-FREE FOR SPECIAL APPLICATION

ISO VG 32, 46, 68, 100

PERFORMANCE STANDARDS

- Fives P-68, P-69 and P-70
- ISO 11158 HM
- DIN 51 524 Part 2 HLP
- ASTM D6158
- SAE MS 1004
- ISO 20763 vane pump tes

Currently available in 200L, 20L, 18L



GEAR OIL

Texas Lubricants' premium Gear Oil, engineered to provide exceptional performance and protection for your gear systems. It is formulated with advanced **EP** additives allowing outstanding high load-carrying properties, resist wear and tear, prevent deposit formation, and protect against high temperatures and extreme pressures. Texas Gear Oil boasts excellent anti-foaming properties and effective rust and corrosion prevention, ensuring optimal gear system performance.

Full product specifications, description and application can be requested from your local distributor.

1. TEXAS TEXGEAR RANGE

EXTREME-PRESSURE INDUSTRIAL GEAR OIL

ISO VG 68, 100, 220, 320, 460, 680

PERFORMANCE STANDARDS

- U.S. Steel 224
- DIN 51517 Part 3

- AGMA 9005-E02
- ISO 12925-1 CKC/CKD
- David Brown Type M, A & E

Currently available in 200L, 20L, 18L

2. TEXAS GEARTRA EPX GL-5

EXTREME-PRESSURE MULTI GRADE AUTOMOTIVE GEAR OIL

EPX 80W90

EPX 85W140

PERFORMANCE STANDARDS

- API GL - 5
- AGMA 9005-E02
- DIN51517 PART 3
- ISO 12925-1 CKC/CKD
- U.S. STEEL 224
- DAVID BROWN TYPE M, A & E

Currently available in 200L, 20L, 18L, 5L, 4L, 1L



RADIATOR COOLANT

Texas Lubricants' top-of-the-line Organic Acid Technology (OAT) coolant is designed to provide exceptional cooling and protection for your engine. It is formulated with premium-grade monoethylene glycol (MEG) and advanced additives that ensure superior heat transfer, prevent rust and corrosion, and provide long-lasting protection for your engine components. Its excellent thermal stability and high boiling point make it an ideal choice for high-performance engines, while its low freezing point protects against extreme cold temperatures. Our coolant is also compatible with a range of metals and gaskets, making it a versatile option for different engine types. Choose our MEG-based coolant for optimal engine cooling and protection, even in the most demanding conditions.

Full product specifications, description and application can be requested from your local distributor.

TEXAS LONG-LIFE RADIATOR COOLANT

PREMIUM OAT COOLANT

25%, 50%, 100% CONC.

PERFORMANCE STANDARDS

- BS6580
- BS 6580:2010
- ASTM D3306
- Chinese GB 29743-2013
- Chinese NB/SH/T 0521- 2010

Currently available in 200L, 20L, 18L,

1L Available for 25% Conc.



GREASES

Texas Lubricants' Grease is designed to provide superior lubrication and protection for your machinery. It is formulated with premium base oils and advanced additives that offer excellent wear resistance, extreme pressure protection, and rust and corrosion prevention. Its high dropping point and excellent thermal stability ensure consistent lubrication even under high temperatures, and its water resistance properties provide optimal protection in wet conditions. Our Grease is versatile and suitable for a range of applications, including automotive, industrial, and marine equipment. Choose our Grease for long-lasting protection and performance for your machinery, even in the most challenging operating environments.

Full product specifications, description and application can be requested from your local distributor.

1. TEXAS LITHIUM EP GREASE

HIGH QUALITY MULTI PURPOSE LITHIUM BASED

NLGI 2, NLGI 3

PERFORMANCE STANDARDS

TEXAS GREASE LEP 2

DIN 51502 KP2K-30

ISO 12924 L-XC(F)CHB2

TEXAS GREASE LEP 3

DIN 51502 KP3K-30

ISO 12924 L-XC(F)CHB3

Currently available in 15KG, 180KG

2. TEXAS LITHIUM COMPLEX EP GREASE

HIGH QUALITY MULTI PURPOSE HIGH TEMPERATURE LITHIUM COMPLEX BASED

NLGI 2, NLGI 3

PERFORMANCE STANDARDS

TEXAS LCEP 2

DIN 51502 KP2R-30

ISO 12924 L-XC(F)FIB2

TEXAS LCEP 3

DIN 51502 KP3R-30

ISO 12924 L-XC(F)FIB3

Currently available in 15KG, 180KG

This is the last part of the press release, where you will create a brief company background, what you're known for in the industry, and how long you've been around. Links to your website or social media channels may also go here.

**CONTACT : STEVEN
+60 167701886**

WWW.TEXASLUB.COM