



PRODUCT DATA SHEET

Issue on 14 April 2017

Texas Petrochemical Asia Pacific Pte Ltd

Singapore 629170

Tel: 65-6262 6538

Fax: 65-6262 6537

Website: www.texaslub.com

TEXAS TEXMARINE LS 200 TBN 20 SAE 50

Superior Quality Cylinder Lubricant

DESCRIPTION

TEXAS TEXMARINE LS 200 is alkaline marine diesel engine cylinder lubrication suitable for low speed two-stroke diesel engines and running on low Sulphur distillate fuels and all ultra-low Sulphur fuel oils.

PERFORMANCE STANDARDS

- API CF

MAIN APPLICATION

- Cylinder Lubrication of low and Ultra-Low Sulphur distillate fuels and ultra-low Sulphur fuel oils with Sulphur Content < 0.10% specifically for vessels operating in Emission Control Areas (ECA).

BENEFITS

- High level of dispersion and detergency
- Excellent resistance to oxidation at high temperatures
- High load carrying capacity
- Excellent anti-wear, anti-rust and anti-foaming properties

TYPICAL PROPERTIES

TEXMARINE LS 200	SAE 50
Density, kg/Litre @ 15°C	0.905
Kinematic Viscosity, mm ² /s @ 40°C	223.9
Kinematic Viscosity, mm ² /s @ 100°C	19.0
Viscosity Index	100
Pour Point, °C	-12
Flash Point COC, °C	230
TBN	20